

TURAM-075110040510

Active Frequency Multiplier,
X4,75-110 GHz, 5 dBm Output Power

Feature:

- Output Frequency:75-110 GHz
- Output Power : 5 dBm Typ
- Low power consumption

电气特性 Electrical Specifications:

参数 Parameter	Min	Typ	Max	单位 Units
输出频率 Output Frequency	75		110	GHz
输出功率 Output Power	3	5	10	dBm
输入频率 Input Frequency	18.75		27.5	GHz
输入功率 Input Power	2	3	5	dBm
倍频次数 Multiply Factor		4		Time
输入驻波 Input VSWR		2		:1
输出驻波 Output VSWR		2.5		:1
供电电压 DC Voltage	5.5			V
供电电流 DC Supply Current		530		mA

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输出接口 Output Connector	WR-10/UG-387/U	
输入接口 Input Connector	2.92mm Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	48*56*60	mm

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	5.5V
输入功率 RF Input Power	+5 dbm



Unit: mm



温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-10		+65	℃
存储温度 Non-operating Temperature	-25		+75	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号 Revision
TURAM-075110040510	Active Multiplier,X4,75-110GHz, Output Power:5dBm,WR-10/UG-387/U,2.92mm Female	Rev.1.1