

TURAM-086106081010

**Active Frequency Multiplier**  
**X8,86-106GHz, 10dBm Output Power**

**Feature:**

- Output Frequency:86-106GHz
- Output Power: 10dBm Typ
- Low power consumption

**电气特性 Electrical Specifications:**

参数 Parameter	Min	Typ	Max	单位 Units
输出频率 Output Frequency	86		106	GHz
输出功率 Output Power		10		dBm
输入频率 Input Frequency	10.75		13.25	GHz
输入功率 Input Power	3		5	dBm
倍频次数 Multiply Factor		8		Time
输入驻波 Input VSWR		2		:1
输出驻波 Output VSWR		2		:1
供电电压 DC Voltage	5			V
供电电流 DC Supply Current		130		mA

**机械特性 Mechanical Specifications:**


参数 Parameter	指标 Value	单位 Units
输出接口 Output Connector	WR-10/UG-387/U	
输入接口 Input Connector	SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	42*24*30	mm

**绝对最大值 Absolute Maximum Ratings:**

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	6V
输入功率 RF Input Power	+6dBm



Unit: mm



### 温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-10		+65	°C
存储温度 Non-operating Temperature	-55		+85	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

### 订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号 Revision
TURAM-086106081010	Active Multiplier,X8,86-106GHz, Output Power:10dBm,WR-10/UG-387/U,SMA Female	Rev.1.1

## 典型曲线 Typical Performance Data:

