

Low Noise Amplifier

18-40GHz/3.5dB NF/36dB Gain/15dBm P1dB

TLLA18G40G-36-35

TURLA18G40G-3635 is a low noise amplifier with a typical small signal gain of 36 dB and a maximum noise figure of 3.5 dB across the frequency range of 18 to 40 GHz. The DC power requirement for the amplifier is +12 V DC/80 mA. The input and output port configuration offers coax adapter structure with 2.92mm female.

- Features:**
- Frequency range: 18-40GHz
 - Gain: 36dB Typ
 - Noise Figure: 3.5dB Max
 - Good Power and Gain Flatness
 - 50 Ohm Matched Input / Output

- Applications:**
- Communication systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	18		40	GHz
小信号增益 Small Signal Gain		36		dB
增益平坦度 Gain Flatness			±2.5	dB
噪声系数 Noise Figure		3.0	3.5	dB
线性输出功率 Output P1dB		15		dBm
杂散 Spurious		-60		dBc
输入驻波 Input VSWR			2.2	:1
输出驻波 Output VSWR			2.2	:1
直流电压 DC Voltage	+8	+12	+15	V DC
直流电流 DC Supply Current		80		mA
阻抗 Impedance	50			Ohms


机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.92mm Female/2.92mmFemale	
直流偏置 DC Bias	Solder Pin	

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+15 V
输入功率 RF Input Power	+15 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing: Unit:mm



***Heat Sink Required During Operation



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.


温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-45		+85	℃
存储温度 Non-operating Temperature	-55		+125	℃
相对湿度 Relative humidity		95		%
海拔 Altitude		50,000		feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TURLA18G40G-3635	Low Noise Amplifier, 18-40GHz, Noise Figure:3.5dB, Gain:36dB,P1dB:15dBm,+12V DC,Without Heatsink	Rev.1.1
TURLA18G40G-3635 HS	Low Noise Amplifier, 18-40GHz, Noise Figure:3.5dB, Gain:36dB,P1dB:15dBm,+12V DC,With Heatsink	Rev.1.1

典型曲线 Typical Performance Data:



Noise Figure vs Frequency

Noise Figure(dB)

典型曲线 Typical Performance Data:

