

Power Amplifier

2-18GHz/43dB Gain/43dBm Psat

TLPA2G18G-43-43

TURPA2G18G-4343 is a power amplifier with a minimum small signal gain of 43 dB and a typical Psat of 43 dBm across the frequency range of 2 to 18 GHz. The DC power requirement for the amplifier is +28 VDC/5 A. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 2-18GHz
- Gain: 43dB Min
- Output Power Psat: 43dBm Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	2-18			GHz
小信号增益 Small Signal Gain	45			dB
增益平坦度 Gain Flatness		±3		dB
饱和输出功率 Output Psat	42.5	43		dBm
杂散 Spurious			-50	dBc
谐波 Harmonic			-10	dBc
输入驻波 Input VSWR			2	:1
直流电压 DC Voltage		28		V DC
直流电流 DC Supply Current			5	A
阻抗 Impedance	50			Ohms




机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流供电接口 DC Supply Connector	Feedthru capacitors	
尺寸 Size	60*60*11(Without heatsink) 188*125*146(With heatsink)	mm
重量 Weight	≤200	g

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+29 V
输入功率 RF Input Power	+3 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing: Unit:mm



温度环境 Environmental Conditions:


参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+50	℃
存储温度 Non-operating Temperature*	-50		+60	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.




订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TURPA2G18G-4343	Power amplifier 2-18GHz, Gain:43dB,Psat:43dBm,+28V DC,Without Heatsink	Rev.1.1
TURPA2G18G-4343 HS	Power amplifier 2-18GHz, Gain:43dB,Psat:43dBm,+28V DC,With Heatsink	Rev.1.1


典型曲线 Typical Performance Data:



典型曲线 Typical Performance Data:



典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.