

Model TURPA50M500M-5047HS

50MHz-500MHz,Gain:50dB,Psat:47dBm

Feature:

- Frequency range: 50MHz-500MHz
- Gain: 50dB Typ
- Psat Output Power: 47 dBm Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

电气特性 Electrical:

参数Parameter	Min.	Typ.	Max.	单位Units
频率范围 Frequency range	50MHz-500MHz			GHz
增益 Gain	47	50		dB
增益平坦度 Gain Flatness		±1dB	±2dB	dB
线性输出功率P1dB	44	46		dBm
饱和输出功率Psat	46	48		dBm
噪声系数Noise Figure		4.5	7	dB
输入驻波 Input VSWR		1.5	2.0	:1
直流电压 DC Voltage		24		V DC
直流电流 DC Supply Current	10			A
阻抗 Impedance	50			Ohms

机械特性 Mechanical :

参数Parameter	指标 Value	单位Units
输入输出接口 Input /Output Connector	SMA Female	
直流偏置 Bias	Solder Pin	
尺寸 Size	152.4X82.6X28.6	mm
重量 Weight	500	g




Available 220V System
Benchtop Amplifier

绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
-------------	----------

外形尺寸Outline Drawing:

Unit: mm



***Heat Sink Required During Operation



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

温度环境 Environmental Conditions:

参数Parameter	Min.	Typ.	Max.	单位Units
操作温度 Operating Temperature	-45		+85	℃
存储温度 Non-operating Temperature	-55		+125	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	30,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
------------------	----------------	-------------

