

Power Amplifier

6-12GHz/30dB Gain/38dBm Psat

TLPA6G12G-30-36

TURPA6G12G-3036 is a power amplifier with typical small signal gain of 30 dB and a typical Psat of 38 dBm across the frequency range of 6 to 12 GHz. The DC power requirement for the amplifier is +28 VDC/2.3 A. The input and output port configuration offers coax adapter structure with SMA Female.

Features:

- Frequency range: 6-12GHz
- Gain: 30dB Min
- Output Power Psat: 38dBm Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	6-12			GHz
增益 Gain	30			dB
增益平坦度 Gain Flatness		±1.5	±2.5	dB
线性输出功率 Output P1dB	36	37		dBm
饱和输出功率 Output Psat		38		dBm
杂散 Spurious		-60		dBc
输入驻波 Input VSWR		1.5	2	:1
输出驻波 Output VSWR		1.5	2	:1
直流电压 DC Voltage		12		V DC
直流电流 DC Supply Current		2.3	2.5	A
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	85*50*12	mm
重量 Weight	300	g

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+12 V
输入功率 RF Input Power	12 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm



温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+50	°C
存储温度 Non-operating Temperature*	-50		+60	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TURPA6G12G-3036	Power amplifier 6-12GHz,Gain30dB,P1dB:36dBm,+12V DC,Without Heatsink.	Rev.1.1
TURPA6G12G-3036 HS	Power amplifier 6-12GHz,Gain30dB,P1dB:36dBm,+12V DC,With Heatsink.	Rev.1.1

典型曲线 Typical Performance Data:

