

Power Amplifier
6-40GHz /32dB Gain/23 dBm Psat

TLPA6G40G-32-22

TURPA6G40G-3222 is a power amplifier with a typical small signal gain of 32 dB and a nominal Psat of 23 dBm across the frequency range of 6 to 40 GHz. The DC power requirement for the amplifier is +12 VDC/0.25 A. The input and output port configuration offers coax adapter structure with 2.92mm female.

Features:

- Frequency range: 6-40GHz
- Gain: 32dB Typ
- Output Power Psat: 23dBm Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	6-40			GHz
小信号增益 Small Signal Gain		32		dB
增益平坦度 Gain Flatness		±2		dB
线性输出功率 Output P1dB	20	22		dBm
饱和输出功率 Output Psat		23		dBm
噪声系数 Noise Figure		6		dB
输入驻波 Input VSWR		1.7		:1
输出驻波 Output VSWR		1.7		:1
直流电压 DC Voltage		12		V DC
直流电流 DC Supply Current		255		mA
阻抗 Impedance	50			Ohms


机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.92mm Female/2.92mm Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	44*36*12(Withoout Heatsink) 65*45*39(With Heatsink)	mm
重量 Weight	25	g

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+13 V
输入功率 RF Input Power	+10 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing: Unit:mm





温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+60	℃
存储温度 Non-operating Temperature*	-50		+70	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TURPA6G40G-3222	Power amplifier 6-40GHz,Gain:32dB,Psat:23dBm, +12V DC,Without Heatsink	Rev.1.1
TURPA6G40G-3222 HS	Power amplifier 6-40GHz,Gain:32dB,Psat:23dBm, +12V DC,With Heatsink	Rev.1.1


典型曲线 Typical Performance Data:

VSWR&Gain vs Frequency

VSWR&Gain

典型曲线 Typical Performance Data:

Gain vs Output Power



P1dB vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.