

Passive Frequency Multiplier

WR-08/X2/90-140GHz/2dBm Output Power

TMPM-090140-0202-08

TURPM-090140020208 is a WR-08 X2 passive multiplier that generates second order harmonics with good harmonic and fundamental suppression. This multiplier requires an input frequency range of 45 to 70 GHz at +15 dBm RF power to yield typical +2 dBm output power at 90 to 140 GHz. The multiplier is equipped with a WR-15 waveguide and UG-385/U-M flange as its input port and a WR-08 waveguide and UG-387/U-M flange as its output port.

Features:

- Output Frequency: 90-140GHz
- Output Power: 2dBm Typ
- Compactness,High Power&Efficiency

Applications:

- Frequency Extenders
- THz Systems
- Source Modules

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
输出频率 Output Frequency	90		140	GHz
输入频率 Input Frequency	45		70	GHz
输出功率 Output Power		2		dBm
输入功率 Input Power		15	18	dBm
倍频次数 Multiply Factor		2		

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输出接口 Output Connector	WR-08/UG-387/U	
输入接口 Input Connector	WR-15/UG-385/U	
尺寸 Size	20*20*20	mm

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
输入功率 RF Input Power	+19 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm



ESD Protection: Strictly

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-10		+65	°C
存储温度 Non-operating Temperature	-45		+85	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TURPM-090140020208	Passive Frequency Doubler X2,90-140GHz, 2dBm Output Power,WR-08	Rev.1.1