

C

C

Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-40GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.25
Insertion Loss	≤0.05* $\sqrt{f_GHz}$
Operating Temperature	- 45~+125 °C
Material & Coat-Plating	
Inner Conductor	BERYLLIUM COPPER
Dielectric	PEI
	STAINLESS STEEL

A

A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN CHK	Turpanic Co, Ltd ,Inc	
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Model	
		PRODUCT SPEC	1.0/2.92-JK 1.0Male 2.92Female Connector	
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4
				DRAWING NO
		CUSTOMER DRAWING SCALE 4: SCALE 4: 1 SHEET1 OF 1 RVE 1		