



B Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC~67GHz
Dielectric Withstanding Voltage	500V
VSWR	≤1.50
Insertion Loss	≤1.0dB
Operating Temperature	- 55~+125°C
Material & Coat-Plating	
A Inner Conductor	BE-CU, Gold Plated
Dielectric	PEI

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN CHK	Turpanic Co, Ltd ,Inc		
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED		Product Model		
	0 PLC ±0.25	APVD	1.85-JWKG		
	1 PLC ±0.15	PRODUCT SPEC	1.85mm Male-RA to 1.85mm Female adaptor		
	2 PLC ±0.12				
	3 PLC ±				
	3 PLC ±	APPLICATION SPEC			
	ANGLES ±1°				
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4	DRAWING NO



Turpanic Co, Ltd
Email: johnny@turpanic.com
Mob/WeChat/WhatsApp: +8613088887527

—

C

—

B

—

A

—

C

—

B

—

A