



C

C

B

Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-50 GHz
Dielectric Withstanding Voltage	1000V
VSWR	1.15typ
Insertion Loss	0.05* $\sqrt{f_{GHz}}$
Operating Temperature	- 55~+165 °C
Material & Coat-Plating	
Inner Conductor	Beryllium Copper, Gold
Dielectric	PEI
Stainless Steel, Passivated	

A

A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc				
		CHK					
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED		Product Model 2.4/1.85-JJ 2.4 Male to 1.85 Male Adaptor				
	0 PLC	±0.25			PRODUCT SPEC		
	1 PLC	±0.15					
	2 PLC	±0.12					
	3 PLC	±	APPLICATO N SPEC				
	3 PLC	±					
	ANGLES	±1°					
MATEIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4	DRAWING NO	A	
CUSTOMER DRAWING					SCALE 4: SCALE 4: 1		SHEET1 OF 1