



Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-50 GHz
Dielectric Withstanding Voltage	1000V
VSWR	1.15typ
Insertion Loss	0.05* $\sqrt{f_GHz}$
Operating Temperature	- 55~+165 °C
Material & Coat-Plating	
Inner Conductor	Beryllium Copper, Gold
Dielectric	PEI
	Stainless Steel, Passivated

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN CHK	Turpanic Co, Ltd ,Inc	
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED		Product Model	
	0 PLC ±0.25	1 PLC ±0.15	2.4/1.85-KJ	
	2 PLC ±0.12	PRODUCT SPEC	2.4 Female to 1.85 Male Adaptor	
	3 PLC ±	APPLICATION SPEC		
	3 PLC ±			
	ANGLES ±1°		SIZE A4	GAGE CODE 0T8L4
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	DRAWING NO	
CUSTOMER DRAWING			SCALE 4:SCALE 4: 1	SHEET1 OF 1 RVE 1