



C

C

B

B

Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-50 GHz
Dielectric Withstanding Voltage	1000V
VSWR	1.15typ
Insertion Loss	0.05* $\sqrt{f_{GHz}}$
Operating Temperature	- 55~+165 °C
Material & Coat-Plating	
Inner Conductor	Beryllium Copper, Gold
Dielectric	PEI
Stainless Steel, Passivated	

A

A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc			
		CHK				
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED		Product Model 2.4/1.85-KK 2.4 Female to 1.85 Female Adaptor			
	0 PLC	±0.25			PRODUCT SPEC	
	1 PLC	±0.15				
	2 PLC	±0.12				
	3 PLC	±	APPLICATO N SPEC			
	3 PLC	±				
	ANGLES	±1°				
MATEIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4	DRAWING NO	A
CUSTOMER DRAWING SCALE 4: SCALE 4: 1 SHEET1 OF 1 RVE 1						