

C

B

Electrical & Environmental Characteristics	
Impedance	50 Ω
Insulation Resistance	5000 MΩ
Operating Frequency	DC~40GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.15
Insertion Loss	≤0.05* $\sqrt{f_GHz}$
Operating Temperature	- 55~+165℃
Material & Coat-Plating	
Inner Conductor	Beryllium Copper, Gold

A

5	2. 92-KFD50212-059	0.30 [0.012]	1.5 [0.059]
6	2. 92-KFD50212-079	0.30 [0.012]	2 [0.079]
7	2. 92-KFD50212	0.30 [0.012]	7 [0.276]
8	2. 92-KFD50212-354	0.30 [0.012]	9 [0.354]
9	2. 92-KFD50212-472	0.30 [0.012]	12 [0.472]
10	2. 92-KFD50212-50	0.30 [0.012]	12.7 [0.500]
11	2. 92-KFD50217-269	0.44 [0.017]	6.84 [0.269]
12	2. 92-KFD50217-295	0.44 [0.017]	7.5 [0.295]
13	2. 92-KFD50220-590	0.50 [0.020]	15 [0.590]
14	2. 92-KFD5022502	0.64 [0.025]	6.84 [0.269]
15	2. 92-KFD5022501	0.64 [0.025]	10.92 [0.430]
16	2. 92-KFD50225-1181	0.64 [0.025]	30 [1.181]
17	2. 92-KFD50230	0.75 [0.030]	30 [1.181]
18	2. 92-KFD50243-590	1.10 [0.043]	15 [0.590]
19	2. 92-KFD50250-319	1.27 [0.050]	8.1 [0.319]
20	2. 92-KFD50250-314	1.27 [0.050]	8 [0.314]
21	2. 92-KFD50250-393	1.27 [0.050]	10 [0.393]

C

B

A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd		,Inc
		CHK			
Unit	TOLERANCES UNLESS OTHERWISE SPECIFIED	APVD	Product Model		
mm			2.92-KFD50225-1181		
	0 PLC ±0.25	PRODUCT SPEC	2.92mm Female Flange Connector		
	1 PLC ±0.15				
	2 PLC ±0.12				
	3 PLC ±-				
	3 PLC ±-	APPLICATO N SPEC			
	ANGLES ±1°				
MATEIAL	FINISH	WEIGHT	SIZE A4	GAGE CODE OT8L4	DRAWING NO