

C

C

B

B

Electrical & Environmental Characteristics	
Impedance	50 Ω
Insulation Resistance	5000 MΩ
Operating Frequency	DC~40GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.15
Insertion Loss	≤0.05* $\sqrt{f\_GHz}$
Operating Temperature	- 55~+165 °C
Material & Coat-Plating	
Inner Conductor	Beryllium Copper, Gold
Dielectric	PEI 1000
Body	Stainless Steel,Passivated

A

A

No.	Model	D1(Diameter1)	D2(Diameter2)	L1(Length1)	L2(Length2)
1	2.92-KFD61304	1.67 [0.066]	0.30 [0.012]	1.4 [0.055]	1.5 [0.059]
2	2.92-KFD61305	1.67 [0.066]	0.30 [0.012]	3 [0.118]	1.5 [0.059]
3	2.92-KFD613058	1.67 [0.066]	0.30 [0.012]	3 [0.118]	4.5 [0.177]
4	2.92-KFD613162	1.80 [0.071]	0.55 [0.022]	6.3 [0.248]	11.9[0.468]

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc	
		CHK		
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED	APVD	Product Model	
	0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	PRODUCT SPEC	2.92-KFD61304 2.92mm Female Flange Connector	
MATEIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE OT8L4
			DRAWING NO	
CUSTOMER DRAWING			SHEET1 OF 1	
			RVE 1	