

C

B

Electrical & Environmental Characteristics	
Impedance	50 Ω
Insulation Resistance	5000 MΩ
Operating Frequency	DC~40GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.15
Insertion Loss	≤0.05* $\sqrt{f_{GHz}}$
Operating Temperature	- 55~+165 °C
Material & Coat-Plating	
Inner Conductor	Beryllium Copper, Gold
Dielectric	PEI 1000
Body	Stainless Steel,Passivated

A

No.	Model	D1(Diameter1)	D2(Diameter2)	L1(Length1)	L2(Length2)
1	2.92-KFD502050	4.0 [0.157]	0.20 [0.008]	3 [0.118]	1.5 [0.059]
2	2.92-KFD70204	4.0 [0.157]	0.30 [0.012]	1.4 [0.055]	1.5 [0.059]
3	2.92-KFD70205	4.0 [0.157]	0.30 [0.012]	3 [0.118]	1.5 [0.059]
4	2.92-KFD702190	4.0 [0.157]	0.30 [0.012]	3 [0.118]	5 [0.197]
5	2.92-KFD702250	4.0 [0.157]	0.30 [0.012]	3.2 [0.126]	1.5 [0.059]
6	2.92-KFD702031	4.0 [0.157]	0.30 [0.012]	4 [0.157]	1 [0.039]
7	2.92-KFD702110	4.0 [0.157]	0.30 [0.012]	10.1 [0.398]	0.5 [0.020]
8	2.92-KFD702020	4.0 [0.157]	0.38 [0.015]	3 [0.118]	2 [0.079]
9	2.92-KFD702150	4.0 [0.157]	0.60 [0.024]	4 [0.157]	1.27 [0.050]
10	2.92-KFD70211	4.0 [0.157]	0.60 [0.024]	10.1 [0.398]	1.27 [0.050]

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc	
		CHK		
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED	APVD	Product Model 2.92-KFD7021505 2.92mm Female Flange Connector	
	0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	PRODUCT SPEC		
		APPLICATON SPEC		
MATEIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4
			DRAWING NO	
		CUSTOMER DRAWING	SHEET1 OF 1	
			RVE 1	