

C

| No. | Model | D1(Diameter1) | D2(Diameter2) | L1(Length1) | L2(Length2) |
|-----|-----------------|---------------|---------------|--------------|--------------|
| 1 | 2.92-KFD503050 | 4.0 [0.157] | 0.20 [0.008] | 3 [0.118] | 1.5 [0.059] |
| 2 | 2.92-KFD70304 | 4.0 [0.157] | 0.30 [0.012] | 1.4 [0.055] | 1.5 [0.059] |
| 3 | 2.92-KFD70305 | 4.0 [0.157] | 0.30 [0.012] | 3 [0.118] | 1.5 [0.059] |
| 4 | 2.92-KFD7031903 | 4.0 [0.157] | 0.30 [0.012] | 3 [0.118] | 5 [0.197] |
| 5 | 2.92-KFD7032503 | 4.0 [0.157] | 0.30 [0.012] | 3.2 [0.126] | 1.5 [0.059] |
| 6 | 2.92-KFD7030319 | 4.0 [0.157] | 0.30 [0.012] | 4 [0.157] | 1 [0.039] |
| 7 | 2.92-KFD7031102 | 4.0 [0.157] | 0.30 [0.012] | 10.1 [0.398] | 0.5 [0.020] |
| 8 | 2.92-KFD7030202 | 4.0 [0.157] | 0.38 [0.015] | 3 [0.118] | 2 [0.079] |
| 9 | 2.92-KFD7031509 | 4.0 [0.157] | 0.60 [0.024] | 4 [0.157] | 1.27 [0.050] |
| 10 | 2.92-KFD70311 | 4.0 [0.157] | 0.60 [0.024] | 10.1 [0.398] | 1.27 [0.050] |

B

Electrical & Environmental Characteristics

| | |
|---------------------------------|------------------------|
| Impedance | 50 Ω |
| Insulation Resistance | 5000 MΩ |
| Operating Frequency | DC~40GHz |
| Dielectric Withstanding Voltage | 1000V |
| VSWR | ≤1.15 |
| Insertion Loss | ≤0.05* $\sqrt{f_GHz}$ |
| Operating Temperature | - 55~+165 °C |

Material & Coat-Plating

A

| | |
|-----------------|----------------------------|
| Inner Conductor | Beryllium Copper, Gold |
| Dielectric | PEI 1000 |
| Body | Stainless Steel,Passivated |

| | | | | |
|---------------------------------------|---|--------------|---|--------------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT | | DWN CHK | Turpanic Co, Ltd ,Inc | |
| Unit mm | TOLERANCES UNLESS OTHERWISE SPECIFIED | APVD | Product Model | |
| | 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1° | PRODUCT SPEC | 2.92-KFD7031903 2.92mm Female Flange Connector | |
| MATERIAL SEE TABLE | FINISH SEE TABLE | WEIGHT | SIZE A4 | GAGE CODE OT8L4 |
| CUSTOMER DRAWING | | | DRAWING NO | |
| | | | SHEET1 OF 1 | |
| | | | RVE 1 | |