

D

D

C

C

Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC~40GHz
Dielectric Withstanding Voltage	1000V
VSWR	1.25 Max
Insertion Loss	≤0.30dB
Operating Temperature	- 55~+165°C
Material & Coat-Plating	
Inner Conductor	Brass, Gold Plated
Dielectric	PEI
Body&Nut	Stainless Steel, Passivated

B

A

A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc			
		CHK				
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ±- 3 PLC ±- ANGLES ±1°	APVD	Product Model			
		PRODUCT SPEC	2.92/2.4-JJ 2.92mm Male to 2.4mm Male adaptor			
		APPLICATION SPEC				
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE OT8L4	DRAWING NO	
		CUSTOMER DRAWING			SHEET1 OF 1	RVE 1