

D

D

C

C

B

B

Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC~40GHz
Dielectric Withstanding Voltage	1000V
VSWR	1.25 Max.
Insertion Loss	≤0.30dB
Operating Temperature	- 55~+165℃
Material & Coat-Plating	
Inner Conductor	BE-CU, Gold Plated
Dielectric	PEI
Body&Nut	Stainless Steel, Passivated

A

A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd ,Inc				
		CHK					
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ±- 3 PLC ±- ANGLES ±1°	APVD	Product Model 2.92/2.4-KK 2.92mm Female to 2.4mm Female adaptor				
		PRODUCT SPEC					
		APPLICATO N SPEC					
MATEIAL SEE TABLE		FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4		DRAWING NO
	CUSTOMER DRAWING				SHEET1 OF 1	RVE 1	