



C

C

B	Electrical & Environmental Characteristics	
	Impedance	50 Ohm
	Insulation Resistance	5000 MΩ
	Operating Frequency	DC-18GHz
	Dielectric Withstanding Voltage	1000V
	VSWR	1.15 typ
	Insertion Loss	≤0.05* $\sqrt{f_{GHz}}$
	Operating Temperature	- 55~+165℃
A	Material & Coat-Plating	
	Inner Conductor	Beryllium Copper, Gold
	Dielectric	PEI
	Body/Nut	Stainless Steel, Passivated

B

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Turpanic Co, Ltd, Inc			
		CHK				
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Model 2.92/N-JK 2.92 Male to N Female Adaptor			
		PRODUCT SPEC				
		APPLICATION SPEC				
		SIZE A4	GAGE CODE 0T8L4	DRAWING NO		
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	CUSTOMER DRAWING		SCALE 4: 1	SCALE 4: 1
				SHEET1 OF 1	RVE 1	

A