

C

C

| Electrical & Environmental Characteristics | |
|--|------------------------------|
| Impedance | 50 Ohm |
| Insulation Resistance | 5000 MΩ |
| Operating Frequency | DC-33GHz |
| Dielectric Withstanding Voltage | 1000V |
| VSWR | ≤1.15 |
| Insertion Loss | ≤0.05* $\sqrt{f_GHz}$ |
| Operating Temperature | - 45~+125 °C |
| Material & Coat-Plating | |
| Inner Conductor | Beryllium Copper Gold Plated |
| Dielectric | PEI |

A

| | | | | |
|---------------------------------------|--|--------------|---|--------------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT | | DWN CHK | Turpanic Co, Ltd ,Inc | |
| Unit mm | TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1° | APVD | Product Model | |
| | | PRODUCT SPEC | 3.5-2.4-KJ 3.5 Female 2.4 Male Connector | |
| MATERIAL SEE TABLE | FINISH SEE TABLE | WEIGHT | SIZE A4 | GAGE CODE 0T8L4 |
| | | | DRAWING NO | |
| CUSTOMER DRAWING | | | | |

B

A