

C

C

B

B

Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-18GHz
Dielectric Withstanding Voltage	1000V
VSWR	1.15 typ
Insertion Loss	≤0.05* $\sqrt{f_GHz}$
Operating Temperature	- 55~+165 °C
Material & Coat-Plating	
Inner Conductor	Brass, Gold
Dielectric	PEI
Body/Nut	Stainless Steel, Passivated

A

A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN CHK	Turpanic Co, Ltd ,Inc	
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED		Product Model	
	0 PLC ±0.25	1 PLC ±0.15	3.5/N-JJ 3.5 Male to N Male Adaptor	
2 PLC ±0.12	3 PLC ±	PRODUCT SPEC		
	3 PLC ±	APPLICATO N SPEC	SIZE A4	GAGE CODE OT8L4
MATEIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	DRAWING NO	

CUSTOMER DRAWING SCALE 4: SCALE 4: 1 SHEET1 OF 1 RVE 1