

C

C

Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-40GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.2
Insertion Loss	≤0.06* $\sqrt{f\_GHz}$
Operating Temperature	- 55~+165℃
Material & Coat-Plating	
Inner Conductor	Beryllium Copper Gold Plated
Dielectric	PEEK
SUS303 Polished&Passivated	

A

A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN CHK	Turpanic Co, Ltd ,Inc	
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD PRODUCT SPEC	Product Model	
			NMD1.85FNMD2.92M NMD1.85 Female NMD2.9 Male Connector	
MATEIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE OT8L4
				DRAWING NO
		CUSTOMER DRAWING		SCALE 4: 1 SCALE 4: 1 SHEET1 OF 1 RVE 1