

SPDT , Terminated , Coaxial Switches

R12-KF12T40-T, Coaxial Switches , SPDT , 2.92mm , Failsafe , 12VDC , TTL , DC to 40 GHz , Solder Pin , Terminated
 R12-KF24T40-T, Coaxial Switches , SPDT , 2.92mm , Failsafe , 24VDC , TTL , DC to 40 GHz , Solder Pin , Terminated
 R12-KF28T40-T, Coaxial Switches , SPDT , 2.92mm , Failsafe , 28VDC , TTL , DC to 40 GHz , Solder Pin , Terminated

电气参数 Electrical Characteristics:

参数 Parameter	条件 Condition
频率范围 Frequency range	DC-40 GHz
阻抗 impedance	50 Ω
开关模式 Operation mode	Failsafe
开关顺序 Switch sequence	Break before make
切换时间 Switching time	15 ms max
机械寿命 Mechanical life	1 million min
TTL input	0-0.8 V(OFF), 2.4-5 V(ON)
负载功率 Termination power CW	0.5W
额定电压 Rated voltage	12 24 28 VDC
工作电流 Operating current at 23 °C	380 200 170 mA




射频特性 RF Specifications:

频率范围 FREQUENCY RANGE(GHz)	DC-6	6-12	12-18	18-26.5	26.5-32	32-40
插入损耗 INSERTION LOSS (MAX) dB	0.2	0.25	0.4	0.7	0.8	1.0
隔离度 ISOLATION (MIN) dB	70	70	60	55	50	50
电压驻波比 V.S.W.R. (MAX)	1.2:1	1.3:1	1.4:1	1.7:1	1.9:1	2.0:1


环境和物理特性 Environmental And Physical Characteristics:

参数 Parameter	条件 Condition
工作温度范围 Operating temperature range	-25°C to +65°C(Standard) -55°C to +85°C(Optional)
振动 Sine vibration(Operating)	20-2000Hz , 10g
冲击 Shocks(Non Operating)	50g / 11ms, ½ sine
射频接口 RF Connector type	2.92 Female

外形尺寸 Outline Drawing: Unit: mm




原理图 Schematic:



功率曲线图 Average power:

- This graph is based on the following conditions:
- Ambient temperature: + 25 °C
 - Sea level
 - V.S.W.R.: 1 and cold switching

引脚定义 Pin Definition:



Solder Pin		RF Connect Used
Pin NO.	Function	SPDT
1	A1(TTL IN)	NO:J1-COM
	0	NC:J2-COM
2	UNUSED	
3	COM-	
4	+VDC	

标准型号 Part Number:

标准型号 Part Number

额定电压
Rated Voltage


可选项 Option

SPDT


12VDC

典型曲线 Typical Performance Data:

INSERTION LOSS



VSWR



ISOLATION

