

R12-NF12T12-I, Coaxial Switches, SPDT, N, Failsafe, 12VDC, TTL, DC to 12.4 GHz, Solder Pin, Electronic Type Indicator
 R12-NF24T12-I, Coaxial Switches, SPDT, N, Failsafe, 24VDC, TTL, DC to 12.4 GHz, Solder Pin, Electronic Type Indicator
 R12-NF28T12-I, Coaxial Switches, SPDT, N, Failsafe, 28VDC, TTL, DC to 12.4 GHz, Solder Pin, Electronic Type Indicator

电气参数 Electrical Characteristics:

参数Parameter	条件Condition
频率范围 Frequency range	DC-12.4GHz
阻抗 Impedance	50 Ω
开关模式 Operation mode	Failsafe
开关顺序 Switch sequence	Break before make
切换时间 Switching time	15 ms max
机械寿命 Mechanical life	1 million min
TTL input	0-0.8 V(OFF), 2.4-5 V(ON)
工作电压 Nominal operating voltage	12 24 28 VDC
工作电流 Operating current at 23 °C	270 150 110 mA
指示灯额定值 Indicator rating	Electronic Type Indicator Max withstand voltage: 60VDC Max current capacity: 100mA Max "ON" resistance: 16Ω Note: +VDC(i) and COM- must be connected to operate.




射频特性 RF Specifications:

频率范围 FREQUENCY RANGE(GHz)	DC-2	2-4	4-12.4
插入损耗 INSERTION LOSS (MAX) dB	0.2	0.25	0.5
隔离度 ISOLATION (MIN) dB	80	80	60
电压驻波比 V.S.W.R. (MAX)	1.15:1	1.2:1	1.5:1


环境和物理特性 Environmental And Physical Characteristics:

参数Parameter	条件 Condition
工作温度范围 Operating temperature range	-25°C to +65°C(Standard) -55°C to +85°C(Optional)
振动 Sine vibration(Operating)	20-2000Hz, 10g
冲击 Shocks(Non Operating)	50g / 11ms, ½ sine
射频接口 RF Connector type	N Female

外形尺寸 Outline Drawing: Unit: mm



原理图 Schematic:




功率曲线图 Average power:

This graph is based on the following conditions:

- Ambient temperature: + 25 °C
- Sea level
- V.S.W.R.: 1 and cold switching

针脚定义 Pin Definition:



Solder Pin		RF Connect Used
Pin NO.	Function	SPDT
1	+VDC/VDC(i)	
2	COM-	
3	A1(TTL IN)	NO:J1-COM
	0	NC:J2-COM
4	UNUSED	
5	1(IND.)	NO:J1-COM
6	COMi(IND.)(V+)	
7	2(IND.)	NC:J2-COM

标准型号 Part Number:

标准型号 Part Number

额定电压
Rated Voltage

可选项 Option

SPDT

R12-NF12T12-I

12VDC

-S