

1P8T, Terminated, Coaxial Switches

R18-SN12018-DT, Coaxial Switches, 1P8T, SMA, Normally Open, 12VDC, DC to 18 GHz, DSUB-15, Terminated
 R18-SN24018-DT, Coaxial Switches, 1P8T, SMA, Normally Open, 24VDC, DC to 18 GHz, DSUB-15, Terminated
 R18-SN28018-DT, Coaxial Switches, 1P8T, SMA, Normally Open, 28VDC, DC to 18 GHz, DSUB-15, Terminated

电气参数 Electrical Characteristics:

参数Parameter	条件Condition
频率范围 Frequency range	DC-18GHz
阻抗 Impedance	50 Ω
开关模式 Operation mode	Normally Open
开关顺序 Switch sequence	Break before make
切换时间 Switching time	15 ms max
机械寿命 Mechanical life	1 million min
负载功率 Termination power CW	0.5W
额定电压 Rated voltage	12 24 28 VDC
工作电流 Operating current at 23 °C	330 167 140 mA




射频特性 RF Specifications:

频率范围 FREQUENCY RANGE(GHz)	DC-6	6-12	12-18
插入损耗INSERTION LOSS (MAX) dB	0.3	0.4	0.5
隔离度 ISOLATION (MIN) dB	80	70	60
电压驻波比 V.S.W.R. (MAX)	1.3:1	1.4:1	1.5:1


环境和物理特性 Environmental And Physical Characteristics:

参数Parameter	条件 Condition
工作温度范围 Operating temperature range	-25°C to +65°C(Standard) -55°C to +85°C(Optional)
振动 Sine vibration(Operating)	20-2000Hz, 10g
冲击 Shocks(Non Operating)	50g / 11ms, ½ sine
射频接口 RF Connector type	SMA Female

外形尺寸 Outline Drawing: Unit: mm




原理图 Schematic:



功率曲线图 Average power:

- This graph is based on the following conditions:
- Ambient temperature: + 25 °C
 - Sea level
 - V.S.W.R.: 1 and cold switching

针脚定义 Pin Definition:



15PIN D-SUB		RF Connect Used
Pin NO.	Function	SP8T
1	V1	1
2	V2	2
3	V3	3
4	V4	4
5	V5	5
6	V6	6
7	V7	7
8	V8	8
9	COM-	
10-15	UNUSED	

标准型号 Part Number:

标准型号 Part Number


1P8T

额定电压
 Rated Voltage


可选项 Option

典型曲线 Typical Performance Data:

VSWR



INSERTION LOSS



ISOLATION

