

Part No: RAXXA50-S-18


SMA Attenuators • Male to Female • DC – 18 GHz - 50 W

电气特性 ELECTRICAL

- **Frequency Range** DC-18 GHz
- **Attenuation (dB)**
 - 1 through 9.... -1.0/+1.5 dB
 - 10 -1.0/+1.5 dB
 - 20-1.0/+1.5 dB
 - 30-1.0/+1.5 dB
 - 40 -1.0/+1.5 dB
- **VSWR (MAX)**
 - DC – 12.4 GHz..... 1.30 : 1
 - 12.4 – 18 GHz..... 1.35 : 1
- **Impedance** 50 Ohms
- **RF Power Nominal** 50 Watts Average at 25°C
 PEAK: 1000 Watts
 (5 μSec Pulse Width , 5% Duty Cycle)

机械特性 MECHANICAL

- **Temperature Range** -55°C - +125°C
- **Connectors** Brass ,Nickel Plated
- **Connector Pins** Beryllium Copper, Gold Plated
- **Housing** Black, Finned Aluminum
- **Insulators** PTFE, Virgin Electrical Grade



Connector: SMA and N are optional.
 Unit:mm

订货信息 ORDER

Model Number : RAXXA50-S-18
 └──────────┬──────────┘
 dB Value