

Part No: RAXXA50-S-4


SMA Attenuators • Male to Female • DC – 4 GHz - 50 W

电气特性 ELECTRICAL

- **Frequency Range** DC – 4 GHz
- **Attenuation (dB)**
 - 1 through 9 ± 0.75 dB
 - 10± 0.75 dB
 - 20 ± 0.75 dB
 - 30 ± 0.75 dB
 - 40 ± 0.75 dB
- **VSWR (MAX)**
 - DC – 2 GHz..... 1.30 : 1
 - 2 – 3 GHz.....1.30 : 1
 - 3 – 4 GHz.....1.35 : 1
- **Impedance** 50 Ohms
- **RF Power Nominal** 50 Watts Average at 25°C
 PEAK: 10000 Watts
 (5 μSec Pulse Width , 0.5% Duty Cycle)

机械特性 MECHANICAL

- **Temperature Range** -55°C - +125°C
- **Connectors** Brass ,Nickel Plated
- **Connector Pins** Beryllium Copper, Gold Plated
- **Body** Black, Finned Aluminum
- **Insulators** PTFE, Virgin Electrical Grade



Connector: SMA,TNC and N are optional.

Unit:mm

订货信息 ORDER

Model Number : RAXXA50-S-4
 └──────────┬──────────┘
 dB Value