

C

C

B

B

Electrical & Environmental Characteristics	
Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-26.5GHz
Dielectric Withstanding Voltage	1000V
VSWR	1.15 typ
Insertion Loss	≤0.05* $\sqrt{f_GHz}$
Operating Temperature	- 55~+165 °C
Material & Coat-Plating	
Inner Conductor	Beryllium Copper, Gold
Dielectric	PTFE
Body/Nut	Stainless Steel, Passivated

A

A

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN CHK	Turpanic Co, Ltd ,Inc	
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED		Product Model	
	0 PLC ±0.25	PRODUCT SPEC	SMA/2.92-KJ	
	1 PLC ±0.15		2.92 Male to SMA Female Adaptor	
	2 PLC ±0.12			
	3 PLC ±	APPLICATION SPEC		
	3 PLC ±			
	ANGLES ±1°			
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4
			DRAWING NO	
		CUSTOMER DRAWING SCALE 4: SCALE 4: 1 SHEET1 OF 1 RVE 1		