

1 | 3 | 4 | 5

D

C

B

A

**Electrical & Environmental**

- Impedance
- Insulation Resistance
- Operating Frequency
- Dielectric Withstanding Voltage
- VSWR
- Insertion Loss
- Operating Temperature

**Material & Coat-PI**

- Inner Conductor
- Dielectric
- Body
- Coupling Nut

© 2014 TURPANIC

VI

Stai  
Stai

s  
z  
8G  
) dB  
°C

lated

ssivated  
ssivated

THIS DRAWING IS A CONTROLLED DOCUMENT

Unit  
mm

TOLERANCES UNLESS OTHERWISE SPECIFIED  
 0 PLC ±0.25  
 1 PLC ±0.15  
 2 PLC ±0.12  
 3 PLC ±  
 3 PLC ±  
 ANGLES ±1°

MATEIAL  
SEE TABLE

FINISH  
SEE TABLE

DWN

CHK

APVD

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

SIZE

A4

Turpanic Co., Ltd

Product Model

SSMA/SMA-JJ  
SSMA male To SMA male Straight Adap

GAGE CODE  
0T8L4

DRAWING NO

SHEET 1 OF 1

,Inc

3 | 4 | 5