

Active Frequency Multiplier

X2/ 20-60GHz /16dBm Output Power/1.85mm Female

Model: TLAM-2060-0216-V

TLAM-2060-0216-V is an active X2 frequency multiplier. The multiplier has an input frequency of 10 to 30 GHz with a typical input power of -2 dBm and an output frequency of 20 to 60 GHz with a minimum output power of +16 dBm. The DC power requirement for the multiplier is +12 V DC/240 mA. The input port configuration is female 2.92mm connector. The output port configuration is female 1.85mm connector.

Features:

- Output Frequency:20-60GHz
- Output Power :16 dBm Min
- Low power consumption
- 50 Ohm Matched Input / Output

Applications:

- Synthesizers
- Local oscillators

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
输出频率 Output Frequency	20		60	GHz
输出功率 Output Power	+16			dBm
输入频率 Input Frequency	10		30	GHz
输入功率 Input Power	-6	-2	+2	dBm
倍频次数 Multiply Factor		2		
谐波 Harmonic		-15		dBc
供电电压 DC Voltage	+8	+12	+15	V
供电电流 DC Supply Current		240		mA

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输出接口 Output Connector	1.85mm Female	
输入接口 Input Connector	2.92mm Female	
直流偏置 DC Bias	Solder Pin	

绝对最大值 Absolute Maximum Ratings:


参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+15 V
输入功率 RF Input Power	+15 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm



*****Heat Sink Required During Operation**



温度环境 Environmental Conditions:


参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-10		+65	°C
存储温度 Non-operating Temperature	-45		+85	°C
相对湿度 Relative humidity		95		%
海拔 Altitude		10,000		feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLAM-2060-0216-V	Active Multiplier, X2, 20-60 GHz , +16 dBm Output Power, 1.85mm Female	Rev.1.0

典型曲线 Typical Performance Data:

Output Power vs Frequency



Harmonic Suppression vs Frequency

