

Low Noise Amplifier

18-40GHz/2.5dB NF/11dB Gain/11dBm P1dB

Model: TLLA18G40G-11-25

TLLA18G40G-11-25 is a low noise amplifier with a typical small signal gain of 11 dB and a nominal noise figure of 2.5 dB across the frequency range of 18 to 40 GHz. The DC power requirement for the amplifier is +8 V DC/30 mA. The input and output port configuration offers coax adapter structure with 2.92mm female.

Features:

- Frequency range: 18-40GHz
- Gain: 11dB Typ
- Noise Figure: 2.5dB Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Communication systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	18		40	GHz
小信号增益 Small Signal Gain		11		dB
增益平坦度 Gain Flatness		±2.0		dB
噪声系数 Noise Figure		2.5	3	dB
线性输出功率 Output P1dB	10	11		dBm
输入驻波 Input VSWR		2	2.5	:1
输出驻波 Output VSWR		2	2.5	:1
直流电压 DC Voltage		+8	+12	V DC
直流电流 DC Supply Current		30		mA
阻抗 Impedance		50		Ohms


机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.92mm Female/2.92mm Female	


绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+12 V
输入功率 RF Input Power	+10 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing: Unit:mm



*****Heat Sink Required During Operation**



温度环境 Environmental Conditions:


参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude		10,000		feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			

订货信息 Ordering Information:


标准型号 Base Number	描述 Description	版本号 Revision
TLLA18G40G-11-25	Low Noise Amplifier, 18-40GHz, Noise Figure:2.5dB, Gain:11 dB,P1dB:11dBm,+8V DC,Without Heatsink	Rev.1.1
TLLA18G40G-11-25-HS	Low Noise Amplifier, 18-40GHz, Noise Figure:2.5dB, Gain:11 dB,P1dB:11dBm,+8V DC,With Heatsink	Rev.1.1

典型曲线 Typical Performance Data:

Gain&VSWR vs Frequency




Noise Figure vs Frequency




典型曲线 Typical Performance Data:

Gain vs Output Power



P1dB vs Frequency



P3dB vs Frequency

P3dB (dBm)