

Low Noise Amplifier

1-40GHz/6.0dB NF/30dB Gain/22dBm P1dB

Model: TLLA1G40G-30-60

TLLA1G40G-30-60 is a low noise amplifier with a typical small signal gain of 30 dB and a nominal noise figure of 6.0 dB across the frequency range of 1 to 40 GHz. The DC power requirement for the amplifier is +9 V DC/360 mA. The input and output port configuration offers coax adapter structure with 2.92mm female.

Features:

- Frequency range: 1-40GHz
- Gain: 30dB Typ
- Noise Figure: 6.0dB Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Communication systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	1		40	GHz
小信号增益 Small Signal Gain	29	30		dB
噪声系数 Noise Figure		6		dB
线性输出功率 Output P1dB		22		dBm
饱和输出功率 Output Psat		23		dBm
输入驻波 Input VSWR		1.6		:1
输出驻波 Output VSWR		1.8		:1
直流电压 DC Voltage		+9	+12	V DC
直流电流 DC Supply Current		360		mA
阻抗 Impedance		50		Ohms


机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.92mm Female/2.92mm Female	
直流偏置 DC Bias	Solder Pin	

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+12V
输入功率 RF Input Power	0 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing: Unit:mm



*****Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude		10,000		feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLLA1G40G-30-60	Low Noise Amplifier, 1-40GHz, Noise Figure:6.0dB, Gain: 30dB,P1dB:22dBm,+9V DC,Without Heatsink	Rev.1.1
TLLA1G40G-30-60-HS	Low Noise Amplifier, 1-40GHz, Noise Figure:6.0dB, Gain: 30dB,P1dB:22dBm,+9V DC,Without Heatsink	Rev.1.1