

## Low Noise Amplifier

26-40GHz/5.0dB NF/35dB Gain/21dBm P1dB

Model: TLLA26G40G-35-50

TLLA26G40G-35-50 is a low noise amplifier with a minimum small signal gain of 35 dB and a nominal noise figure of 5.0 dB across the frequency range of 26 to 40 GHz. The DC power requirement for the amplifier is +12 V DC/200 mA. The input and output port configuration offers coax adapter structure with 2.92mm female.

### Features:

- Frequency range: 26-40GHz
- Gain: 35dB Min
- Noise Figure: 5.0dB Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

### Applications:

- Communication systems

## 电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	26		40	GHz
小信号增益 Small Signal Gain	35			dB
增益平坦度 Gain Flatness		±2.0		dB
噪声系数 Noise Figure		5		dB
线性输出功率 Output P1dB		21		dBm
输入驻波 Input VSWR		2		:1
输出驻波 Output VSWR		2		:1
直流电压 DC Voltage	+8	+12		V DC
直流电流 DC Supply Current		200		mA
阻抗 Impedance		50		Ohms

## 机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.92mm Female/2.92mm Female	

## 绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+20 V
输入功率 RF Input Power	+15 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

## 外形图 Outline Drawing: Unit:mm



**\*\*\*Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

## 温度环境 Environmental Conditions:


参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude		50,000		feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			

### 订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLLA26G40G-35-50	Low Noise Amplifier, 26-40GHz, Noise Figure:5.0dB, Gain:35dB,P1dB:21dBm,+12V DC,Without Heatsink	Rev.1.1
TLLA26G40G-35-50-HS	Low Noise Amplifier, 26-40GHz, Noise Figure:5.0dB, Gain:35dB,P1dB:21dBm,+12V DC,With Heatsink	Rev.1.1

### 典型曲线 Typical Performance Data:

#### Gain&VSWR vs Frequency




#### Noise Figure vs Frequency


Noise Figure (dB)

## 典型曲线 Typical Performance Data:

### Gain vs Output Power



### P1dB vs Frequency



### P3dB vs Frequency

P3dB (dBm)