

0.1-26GHz, Gain:15dB, P1dB:23dBm

Feature:

- Ultra Wide Band: 0.1-26GHz
- Gain:15dB Typ
- P1dB Output Power:23dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

电气特性 Electrical Specifications:

参数Parameter	Min	Typ	Max	单位Units
频率范围 Frequency range	0.1-26			GHz
增益 Gain		15		dB
增益平坦度 Gain Flatness		±1.5		dB
线性输出功率 Output P1dB		23		dBm
噪声系数 Noise Figure		5		dB
输入驻波 Input VSWR		2		:1
输出驻波 Output VSWR		2		:1
直流电压 DC Voltage	+10	+12	+15	V DC
直流电流 DC Supply Current		200		mA
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:

参数Parameter	指标 Value	单位Units
输入输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	44*36*12	mm
重量 Weight	/	g


绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+15V



Available 220V System

Unit: mm



***Heat Sink Required During Operation




温度环境 Environmental Conditions:

参数Parameter	Min	Typ	Max	单位Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
TLPA0.1G26G-15-23	Power amplifier 0.1-26GHz,Gain:15dB,P1dB:23dBm,+12V DC,Without Heatsink.	Rev.1.1

Gain&VSWR vs Frequency




Noise Figure vs Frequency



Gain vs Output Power

Gain(dB)

P1dB vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.