

## 2.2-2.4GHz, Gain:30dB, Psat:40dBm

### Feature:

- Ultra Wide Band:2.2-2.4GHz
- Gain:30dB Min
- Psat Output Power:40dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

### 电气特性 Electrical Specifications:

参数Parameter	Min	Typ	Max	单位Units
频率范围 Frequency range	2.2-2.4			GHz
增益 Gain	30	33		dB
增益平坦度 Gain Flatness		±0.5	±1	dB
饱和输出功率 Output Psat	40	43		dBm
杂散 Spurious		-65	-60	dBc
输入驻波 Input VSWR		1.3	1.5	:1
输出驻波 Output VSWR			2	:1
直流电压 DC Voltage	+18	+28	+36	V DC
直流电流 DC Supply Current		0.7	3	A
阻抗 Impedance	50			Ohms

### 机械特性 Mechanical Specifications:

参数Parameter	指标 Value	单位Units
输入输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	170*140*40	mm
重量 Weight	1.3	Kg


### 绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+36V



Available 220V System

Unit: mm



**\*\*\*Heat Sink Required During Operation**




**温度环境 Environmental Conditions:**

参数Parameter	Min	Typ	Max	单位Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	30000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


**订货信息 Ordering Information:**

标准型号 Part Number	描述 Description	版本号Revision
------------------	----------------	-------------


## Input VSWR vs Frequency




## Gain vs Frequency




## Gain vs Output Power



## P1dB&P3dB&P5dB vs Frequency



## 2nd Harmonics vs Output Power



## 3rd Harmonics vs Output Power

