

Active Frequency Multiplier,
X2,71-76GHz, 20dBm Output Power

Feature:

- Output Frequency:71-76GHz
- Output Power :20 dBm Typ
- Low power consumption

电气特性 Electrical Specifications:

参数 Parameter	Min	Typ	Max	单位 Units
输出频率 Output Frequency	71		76	GHz
输出功率 Output Power		20		dBm
输入频率 Input Frequency	35.5		38	GHz
输入功率 Input Power		0		dBm
倍频次数 Multiply Factor		2		Time
供电电压 DC Voltage	12			V
供电电流 DC Supply Current		450		mA

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输出接口 Output Connector	WR-12/UG-387/U	
输入接口 Input Connector	2.92mm Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	39*26*20	mm


绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	13V
输入功率 RF Input Power	5dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



Available 220V System
Benchtop Amplifier

Unit: mm



温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-10		+65	℃
存储温度 Non-operating Temperature	-25		+75	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号 Revision
TMAM-071076-0220-12	Active Multiplier,X2,71-76GHz, Output Power:20dBm,WR-12/UG-387/U,2.92mm Female	Rev.1.1