

Waveguide to Coax Adapter, End Launch

WR-10/1.0mm Female/75-110 GHz

TL-10WCA1.0E-CU

Features:

- Operating Frequency 75 to 110GHz
- Lower Insertion Loss and VSWR
- Instrumentation Grade
- DC Short Circuit

Applications:

- Test Lab
- Instrumentations
- Sub-assemblies

电气特性 Electrical Characteristics:


参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency Range	75		110	GHz
驻波 VSWR			1.5	:1
插损 Insertion Loss			1	dB
耐功率 Power Handling			2	W

环境和机械特性 Environmental And Physical Characteristics:

类型 Description	参数 Parameter	单位 Units
材质 Material	Copper	
表面处理 Finish	Gold Plated	
同轴接口 Coax Connector	1.0mm Female	
波导 Waveguide	WR10/UG-387/U-M	

外形图 Outline Drawing:

Unit:mm




订货信息 Ordering Information:


标准型号 Base Number	描述 Description	版本号 Revision
TUR-10WCA1.0ECU	Waveguide to Coax Adapter, End Launch WR10/1.0mm Female,75-110GHz	Rev.1.1

典型曲线 Typical Performance Data:

VSWR vs Frequency



典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.