

TURBT-16K43G50KS

TURBT-16K43G50KS is a bias tee that operates from 16 kHz to 43 GHz. The bias tee offers 3.0 dB insertion loss and -12 dB return loss. The bias tee can handle up to +50 VDC bias voltage and 500 mA current. The RF ports are equipped with 2.92 mm female connectors. Other connector types are available under different model numbers.

Features:

- Ultra Wide Band:16KHz-43GHz
- Low Insertion Loss
- High Voltage
- High Current Capacity

Applications:

- Test Lab
- Sub-assemblies
- System Integrations

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	16KHz-43GHz			
插损 Insertion Loss			3	dB
回波损耗 Rreturn Loss		-12		dB
隔离 Isolation		30		dB
直流电压 DC Voltage			50	V DC
直流电流 DC Current			500	mA
耐受功率 Power Handling			1	W

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.92mm Female/2.92mm Female	
直流接口 DC Connector	SMA Female	
壳体材料 Case Material	Aluminum	

表面处理

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+50 V
输入功率 RF Input Power	+30 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing: Unit:mm



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE

温度环境 Environmental Conditions:


参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:



标准型号 Base Number	描述 Description	版本号 Revision
TURBT-16K43G50KS	Broadband Bias Tee 2.92mm,16KHz-43GHz,+50V	Rev.1.1

- Notes:
- 1. All data taken @ +23° C unless otherwise specified.
 - 2. Dimensions and specifications may be changed without prior notice.



典型曲线 Typical Performance Data:



典型曲线 Typical Performance Data:




典型曲线 Typical Performance Data:




典型曲线 Typical Performance Data:



DC to Com Isolation vs Frequency




DC to RF Isolation vs Frequency



典型曲线 Typical Performance Data:



典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.