

TURDA0.1G3G-1278

The TURDA0.1G3G-1278 is an broadband digitally controlled electrical attenuator operating from 0.1 to 3 GHz. The attenuator exhibits 7 dB typical insertion loss and offers 127.5 dB nominal attenuation control range in 0.5 dB steps under a 8-bit digital control. The control speed of the attenuator is typically 50 ns. The RF input and output ports are female SMA female coax connectors, and a male J30J-15ZKP port is employed for providing the control signal and DC bias.

Features:

- Ultra Wide Band: 0.1-3GHz
- 8-Bit, 0.5 dB LSB, 127.5 dB Range
- Low Insertion Loss
- High Attenuator Accuracy

Applications:

- Radar Systems
- Communication Systems
- Testing Equipment

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	0.1-3			GHz
插损 Insertion Loss		7	8.5	dB
衰减范围 Attenuation Range	127.5			dB
控制位数 Control Bit TTL	8			Bit
衰减步进 Attenuation Step	0.5			dB
切换速度 Switch Speed		50		ns
输入驻波 Input VSWR		1.9		:1
输出驻波 Output VSWR		1.9		:1
最大输入功率 Input Max Power	25			dBm
直流电压 DC Voltage	+5			V DC
直流电流 DC Supply Current			50	mA
阻抗 Impedance	50			Ohms


机械特性 Mechanical Specifications:

描述 Description	参数 Parameter	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
DC控制接口 DC control interface	J30J-15ZKP	
尺寸 Size		mm
重量 Weight	/	g

绝对最大值 Absolute Maximum Ratings :

描述 Description	参数 Parameter	单位 Units
供电偏置电压 Supply Bias Voltage	+5 (±5%)	V
射频输入功率 RF Input Power	25	dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V	

外形图 Outline Drawing: Unit:mm



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE

加电接口和真值表 Supply Conector and Truth Table(J30J-15ZKP):

J30J-15ZKP			
引脚Pin#	功能Function	引脚Pin#	功能Function
1	+5V	9	GND
2	+5V	10	GND
3	GND	11	GND
4	C1	12	C5
5	C2	13	C6
6	C3	14	C7
7	C4	15	C8
8	GND		


真值表 Truth Table								
TTL Control Input								Signal Path State
C1	C2	C3	C4	C5	C6	C7	C8	
0	0	0	0	0	0	0	0	Reference
1	0	0	0	0	0	0	0	0.5
0	1	0	0	0	0	0	0	1
0	0	1	0	0	0	0	0	2
0	0	0	1	0	0	0	0	4
0	0	0	0	1	0	0	0	8
0	0	0	0	0	1	0	0	16
0	0	0	0	0	0	1	0	32
0	0	0	0	0	0	0	1	64
1	1	1	1	1	1	1	1	127.5

温度环境 Environmental Conditions:


参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-10		+65	℃
存储温度 Non-operating Temperature	-45		+85	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:


典型曲线 Typical Performance Data:



0.5dB:




1dB:




典型曲线 Typical Performance Data:


2dB:



4dB:




8dB:




典型曲线 Typical Performance Data:

16dB:



32dB:



64dB:

