

IQ Mixer

RF:10-40 GHz/LO:10-40 GHz/IF:DC-12 GHz

TLIQ-1040-12-K

TURIQ-104012K is an ultra-broadband mixer spanning 10 to 40 GHz on the RF and LO ports with an IF from DC to 12 GHz.Up to 24 dBc of image rejection is available due to the excellent phase and amplitude balance of its on-chip LO quadrature hybrid.

Features:

- RF/LO coverage : 10-40 GHz
- IF operation : DC-12 GHz
- Conversion loss: -12dB Typ
- LO power : 10dBm Typ
- Image Rejection : 24dBc Typ

Applications:

- Single Sideband and Image Rejection Mixing
- IQ Modulation / Demodulation
- Vector Amplitude Modulation
- Band Shifting

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
RF频率 RF Frequency	10		40	GHz
LO频率 LO Frequency	10		40	GHz
LO 驱动功率 LO-Input power	4	10	13	dBm
IF频率 IF Frequency	DC		12	GHz
镜像抑制 Image Rejection @RF/LO:6-26GHz,I+Q:DC-0.2GHz		24		dBc
变频损耗 Conversion Loss @RF/LO:6-26GHz,I/Q:DC-23GHz		-12		dB
LO to IF 隔离 LO to IF Isolation		40		dB
LO to RF 隔离 LO to RF Isolation		40		dB
RF to IF 隔离 RF to IF Isolation		30		dB

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
RF接口 RF Connector	2.92mm Female	
LO接口 LO Connector	2.92mm Female	
IF接口 IF Connector	SMA Female	
尺寸 Size	17.5*17.5*8(Without Connector)	mm

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
LO 输入功率 LO Input Power	+20 dBm
RF/IF 输入功率 RF/IF Input Power	+2 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing: Unit:mm


温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-45		+85	℃
存储温度 Non-operating Temperature	-55		+100	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			



订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TURIQ-104012K	Image Rejection or I/Q Mixer RF:10-40GHz,LO:10-40GHz,IF:DC-12GHz	Rev.1.1

典型曲线 Typical Performance Data:




典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.