

TURLA-110170356006

110-170GHz, NF:4.8 dB, Gain:33 dB

Feature:

- Ultra Wide Band: 110-170 GHz
- Gain: 33dB Typ
- Noise Figure:4.8dB Typ
- Unconditional stability

电气特性 Electrical Specifications:

参数Parameter	Min	Typ	Max	单位Units
频率范围 Frequency range	110		170	GHz
增益 Gain		33		dB
噪声系数 Noise Figure		4.8		dB
输出功率1dB压缩点 Output P1dB		0		dBm
输入驻波 Input VSWR		2.5		:1
输出驻波 Output VSWR		2		:1
直流电压 DC Voltage		+7		V DC
直流供电 DC power supply		53		mA

机械特性 Mechanical Specifications:

参数Parameter	指标 Value	单位Units
输入接口 Input Connector	WR-06/ UG-387/U	
输出接口 Output Connector	WR-06/ UG-387/U	
供电引脚 Power Supply Pin	Solder Pin	
尺寸 Size	/	mm


绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+7 V
输入功率 RF Input Power	TBD



Available 220V System Benchtop Amplifier

Unit: Inches(mm)




温度环境 Environmental Conditions:

参数Parameter	Min	Typ	Max	单位Units
操作温度 Operating Temperature	-55		+85	°C
存储温度 Non-operating Temperature	-45		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
TURLA-110170356006	Low Noise Amplifier,110-170GHz, Noise Figure:4.8dB, Gain:33dB,+7V DC,WR-06	Rev.1.1

Gain vs Frequency



Noise Figure vs Frequency



VSWR vs Frequency

