

TURLA0.1G18G-1228

TURLA0.1G18G-1228 is a low noise amplifier with a minimum small signal gain of 12 dB and a maximum noise figure of 2.8 dB across the frequency range of 0.1 to 18 GHz. The DC power requirement for the amplifier is +12 V DC/70 mA. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 0.1-18GHz
- Gain: 12dB Min
- Noise Figure: 2.8dB Max
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Communication systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	0.1		18	GHz
小信号增益 Small Signal Gain	12			dB
增益平坦度 Gain Flatness		±2.0		dB
噪声系数 Noise Figure		2.5	2.8	dB
线性输出功率 Output P1dB	12	13		dBm
输入驻波 Input VSWR		2.0		:1
输出驻波 Output VSWR		2.0		:1
直流电压 DC Voltage	+8	+12	+15	V DC
直流电流 DC Supply Current		70		mA
阻抗 Impedance		50		Ohms


机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+15 V
输入功率 RF Input Power	+10 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing: Unit:mm





温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude		10,000		feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TURLA0.1G18G-1228	Low Noise Amplifier, 0.1-18GHz, Noise Figure:2.8dB, Gain:12 dB,P1dB:12dBm,+12V DC,Without Heatsink	Rev.1.0
TURLA0.1G18G-1228 HS	Low Noise Amplifier, 0.1-18GHz, Noise Figure:2.8dB, Gain:12 dB,P1dB:12dBm,+12V DC,With Heatsink	Rev.1.0