

## Low Noise Amplifier

0.1-18GHz/3.0dB NF/12dB Gain/8dBm P1dB

TLLA0.1G18G-12-30

TURLA0.1G18G-1230 is a low noise amplifier with a minimum small signal gain of 12 dB and a maximum noise figure of 3.0 dB across the frequency range of 0.1 to 18 GHz. The DC power requirement for the amplifier is +15 V DC/125 mA. The input and output port configuration offers coax adapter structure with SMA female.

### Features:

- Frequency range: 0.1-18GHz
- Gain: 12dB Min
- Noise Figure: 3.0dB Max
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

### Applications:

- Communication systems

## 电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	0.1		18	GHz
小信号增益 Small Signal Gain	12			dB
增益平坦度 Gain Flatness			±2.0	dB
噪声系数 Noise Figure			3.0	dB
线性输出功率 Output P1dB	8			dBm
输入驻波 Input VSWR		2.0	2.5	:1
输出驻波 Output VSWR		2.0	2.5	:1
直流电压 DC Voltage		+15		V DC
直流电流 DC Supply Current		125		mA
阻抗 Impedance		50		Ohms

## 机械特性 Mechanical Specifications:



参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	

## 绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	TBD
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

## 外形图 Outline Drawing:

Unit:mm



**\*\*\*Heat Sink Required During Operation**

## 温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-30		+75	°C
存储温度 Non-operating Temperature	-45		+85	°C
相对湿度 Relative humidity		95		%
海拔 Altitude		10,000		feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			

## 订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TURLA0.1G18G-1230	Low Noise Amplifier, 0.1-18GHz, Noise Figure:3.0dB, Gain: 12dB,P1dB:8dBm,+15V DC,Without Heatsink	Rev.1.1
TURLA0.1G18G-1230 HS	Low Noise Amplifier, 0.1-18GHz, Noise Figure:3.0dB, Gain: 12dB,P1dB:8dBm,+15V DC,With Heatsink	Rev.1.1