

TURLA0.8G1.6G-3213

TURLA0.8G1.6G-3213 is a low noise amplifier with a typical small signal gain of 32 dB and a nominal noise figure of 0.5 dB across the frequency range of 0.8 to 1.6 GHz. The DC power requirement for the amplifier is +5 V DC/50 mA. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 0.8-1.6GHz
- Gain: 32dB Typ
- Noise Figure: 0.5dB Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Communication systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	0.8		1.6	GHz
小信号增益 Small Signal Gain	27	32		dB
增益平坦度 Gain Flatness		±1.0	±1.75	dB
噪声系数 Noise Figure		0.5	0.6	dB
线性输出功率 Output P1dB	12	13		dBm
输入驻波 Input VSWR		1.4	1.8	:1
输出驻波 Output VSWR		1.4	1.8	:1
直流电压 DC Voltage	+4.85	+5	+6	V DC
直流电流 DC Supply Current		50	60	mA
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	TBD
输入功率 RF Input Power	15 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm





ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-40		+70	°C
存储温度 Non-operating Temperature	-65		+150	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TURLA0.8G1.6G-3213	Low Noise Amplifier, 0.8-1.6GHz, Noise Figure:0.5dB, Gain: 32dB,P1dB:13dBm,+5V DC,Without Heatsink	Rev.1.1
TURLA0.8G1.6G-3213 HS	Low Noise Amplifier, 0.8-1.6GHz, Noise Figure:0.5dB, Gain: 32dB,P1dB:13dBm,+5V DC,With Heatsink	Rev.1.1