

TURLA11.75G12.75G-6013

TURLA11.75G12.75G-6013 is a low noise amplifier with a typical small signal gain of 61 dB and a nominal noise figure of 1.1 dB across the frequency range of 11.75 to 12.75 GHz. The DC power requirement for the amplifier is +12 V DC/70 mA. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 11.75-12.75GHz
- Gain: 61dB Typ
- Noise Figure: 1.1dB Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Communication systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	11.75		12.75	GHz
小信号增益 Small Signal Gain	60	61		dB
增益平坦度 Gain Flatness		±1		dB
噪声系数 Noise Figure		1.1	1.3	dB
线性输出功率 Output P1dB	11			dBm
输入驻波 Input VSWR		1.8	2	:1
输出驻波 Output VSWR		1.8	2	:1
直流电压 DC Voltage		+12		V DC
直流电流 DC Supply Current		70		mA
阻抗 Impedance	50			Ohms


机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+15 V
输入功率 RF Input Power	+15 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing: Unit:mm





ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.



温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude		10,000		feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			


订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TURLA11.75G12.75G-6013	Low Noise Amplifier, 11.75-12.75GHz, Noise Figure:1.1dB, Gain:61dB,P1dB:11dBm,+12V DC,Without Heatsink	Rev.1.1
TURLA11.75G12.75G-6013 HS	Low Noise Amplifier, 11.75-12.75GHz, Noise Figure:1.1dB, Gain:61dB,P1dB:11dBm,+12V DC,With Heatsink	Rev.1.1

典型曲线 Typical Performance Data:



典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.