

TURLA17G40G-3745

TURLA17G40G-3745 is a low noise amplifier with a typical small signal gain of 37 dB and a nominal noise figure of 4.5 dB across the frequency range of 17 to 40 GHz. The DC power requirement for the amplifier is +6 V DC/0.8 A. The input and output port configuration offers coax adapter structure with 2.92mm female.

Features:

- Frequency range: 17-40 GHz
- Gain: 37dB Typ
- Noise Figure: 4.5dB Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Communication systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	17		40	GHz
小信号增益 Small Signal Gain	35	37		dB
增益平坦度 Gain Flatness		±3.5		dB
噪声系数 Noise Figure		4.5	6	dB
线性输出功率 Output P1dB	26.5	28		dBm
饱和输出功率 Output Psat		29		dBm
输入驻波 Input VSWR		2		:1
输出驻波 Output VSWR		2		:1
直流电压 DC Voltage		+6	+8	V DC
直流电流 DC Supply Current		0.8		A
阻抗 Impedance	50			Ohms


机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.92mm Female/2.92mm Female	

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+8 V
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing: Unit:mm





ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-45		+85	℃
存储温度 Non-operating Temperature	-55		+125	℃
相对湿度 Relative humidity		95		%
海拔 Altitude		10,000		feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TURLA17G40G-3745	Low Noise Amplifier, 17-40GHz, Noise Figure:4.5dB, Gain:37 dB,P1dB:28dBm,+6V DC,Without Heatsink	Rev.1.1
TURLA17G40G-3745 HS	Low Noise Amplifier, 17-40GHz, Noise Figure:4.5dB, Gain:37 dB,P1dB:28dBm,+6V DC,With Heatsink	Rev.1.1

典型曲线 Typical Performance Data:

