

TURLA2G8G-3211

TURLA2G8G-3211 is a low noise amplifier with a typical small signal gain of 35 dB and a nominal noise figure of 0.8 dB across the frequency range of 2 to 8 GHz. The DC power requirement for the amplifier is +12 V DC/100 mA. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 2-8GHz
- Gain: 35dB Typ
- Noise Figure: 0.8dB Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Communication systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	2		8	GHz
小信号增益 Small Signal Gain	32	35		dB
增益平坦度 Gain Flatness		±0.5	±1.3	dB
噪声系数 Noise Figure		0.8	1.1	dB
线性输出功率 Output P1dB	13	15		dBm
饱和输出功率 Output Psat		16		dBm
输出三阶交调 Output IP3		25		dBm
驻波 VSWR		1.6	2	:1
直流电压 DC Voltage		+12		V DC
直流电流 DC Supply Current		100	130	mA
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:



参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+14 V
输入功率 RF Input Power	-5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm





ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude		50,000		feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TURLA2G8G-3211	Low Noise Amplifier, 2-8GHz, Noise Figure:0.8dB, Gain:35 dB,P1dB:15dBm,+12V DC,Without Heatsink	Rev.1.1
TURLA2G8G-3211 HS	Low Noise Amplifier, 2-8GHz, Noise Figure:0.8dB, Gain:35 dB,P1dB:15dBm,+12V DC,With Heatsink	Rev.1.1