

## Power Amplifier

0.7-18GHz/37dB Gain/37dBm Psat

TLPA0.7G18G-37-37

TURPA0.7G18G-3737 is a power amplifier with power gain of 37 dB and a nominal Psat of 37 dBm across the frequency range of 0.7 to 18 GHz. The DC power requirement for the amplifier is +28 VDC/3 A. The input and output port configuration offers coax adapter structure with SMA female.

### Features:

- Frequency range: 0.7-18GHz
- Gain: 37dB Min
- Output Power Psat: 37 dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

### Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

## 电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	0.7-18			GHz
功率增益 Power Gain	37			dB
增益平坦度 Gain Flatness		±3.5		dB
饱和输出功率 Output Psat	37			dBm
杂散 Spurious@Pout=37dBm			-60	dBc
谐波 Harmonic@Pout=37dBm		-15	-10	dBc
输入驻波 Input VSWR			2	:1
直流电压 DC Voltage		28		V DC
直流电流 DC Supply Current			3	A
阻抗 Impedance	50			Ohms

## 机械特性 Mechanical Specifications:




参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Feedthru capacitors	
尺寸 Size	60*60*11(Without heatsink) 188*125*146(With heatsink)	mm
重量 Weight	≤200	g

## 绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+29 V
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

## 外形图 Outline Drawing:

Unit:mm



## 温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+60	°C
存储温度 Non-operating Temperature*	-50		+70	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

\*Note: For a wider temperature range, please consult the manufacturer.

## 订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TURPA0.7G18G-3737	Power amplifier 0.7-18GHz,Gain:37dB,Psat:37dBm, +28V DC,Without Heatsink	Rev.1.1
TURPA0.7G18G-3737 HS	Power amplifier 0.7-18GHz,Gain:37dB,Psat:37dBm, +28V DC,With Heatsink	Rev.1.1