

TURPA2700M3200M-3044

2.7-3.2GHz,Gain:30dB,Psat:44dBm

Feature:

- Ultra Wide Band: 2.7-3.2GHz
- Gain:30dB Min
- Psat Output Power: 44dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

电气特性 Electrical Specifications:

参数Parameter	Min	Typ	Max	单位Units
频率范围 Frequency range	2.7-3.2			GHz
增益 Gain	30	33		dB
增益平坦度 Gain Flatness		±1	±1.5	dB
饱和输出功率 Output Psat	44	45		dBm
输入驻波 Input VSWR		1.3	1.5	:1
输出驻波 Output VSWR			2	:1
直流电压 DC Voltage		+28	+30	V DC
直流电流 DC Supply Current		3	4.2	A
阻抗 Impedance	50			Ohms


机械特性 Mechanical Specifications:

参数Parameter	指标 Value	单位Units
输入输出接口Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	170*94*20	mm
重量 Weight	300	g

绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+30V

Unit: mm



***Heat Sink Required During Operation



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

温度环境 Environmental Conditions:

参数Parameter	Min	Typ	Max	单位Units
操作温度 Operating Temperature	-45		+85	℃
存储温度 Non-operating Temperature	-55		+125	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	30,000			feet
震动 Shock / Vibration(MIL-STD-810F)	20g,11ms,saw-tooth			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
------------------	----------------	-------------